


Down Under Assembly (704258-1)

Engineered system to locate the rigging point down a vertical span and under a horizontal distance to access walls under deep cornices, caps or architectural features. Down height available is adjustable from 48 to 96 in., and horizontal (under) reach is 36 in. (914 mm) to 60 in. (1,524 mm) with a 1,500 lb. (680.4 kg) maximum hoist capacity.

Key Features:

- Simple system to set-up and deploy saves time
- Mechanical winch allows for no-power deployment
- With optional drill to speed installation, set-up takes minutes
- More stable construction improves worker confidence and production rates
- More under reach than competitors: Spider offers 5 ft. (1.5 m) vs. their 4 ft. (1.2 m)
- Step-by-step set-up instruction labels eliminate guesswork
- Engineered and fully tested to meet ANSI SPS 1.1
- Assembly includes 704411-1 Hook
- Made by Spider in the USA



For use with 5x5 outriggers, gantry frames, OBSF, and suitable scaffold frames.

Longer down lengths available by special order.

Specifications:	704258-1
Outreach:	Down: 48-96 in. (1,219-2,438 mm) Under: 36-60 in. (914-1,524 mm)
Weight:	291 lb (132 kg)
Max. hoist capacity:	1,500 lb (680.4 kg)
Heaviest piece:	49 lb (22.2 kg)
Aluminum and steel construction	

