Lanyards

Every personal fall arrest system requires a high-quality lanyard as a critical link between the anchorage and the harness. To ensure worker safety, Spider lanyards are manufactured with the highest-quality components available.

- Heavy-duty webbing with tamper-resistant locking snap hooks
- Quality workmanship
- Comfortable design that enhances maneuverability

Internal Shock-Absorbing Y-Lanyards



- · Reduces snagging, dragging and tripping hazards
- · Load indicators on each leg
- Twist lock hook for fast, safe tie-off
- Self-closing
- Self-locking
- Standard gate is rated to 3,600 lb (1,632.9 kg);
 5,000 lb. (2,268 kg) gate also available
- · Larger area to capture anchor point
- User-friendly–easy to use while wearing gloves

Web Lanyards for lightweight ease



Your choice of styles:

- 3 ft (0.9 m) web for use with rope grabs
- 6 ft (1.8 m) web, standard for 6 ft (1.8 m) tie-off
- Adjustable web, from 4-6 ft (1.2-1.8 m), reduces free-fall distance
- Shown with Shock Pack

Web Tieback Lanyard (707792-1)





Tieback safely with the shock absorber and 5,000 lb (2,268 kg) gate load capacity from any angle.

- Meets ANSI Z359.13
- New gate strength allows lanyard to be wrapped back and clamped on itself
- Webbing has minimum breaking strength 8,500 lb (3,856 kg) and is abrasion resistant
- Shown with rescue ring which is not intended for tieback use.

6 ft (1.8 m) Web Lanyard with Shock Pack



Internal Shock-Absorbing Lanyards



- · Lightweight 6 ft (1.8 m) lanyard
- Expands 4-6 ft (1.2-1.8 m)
- Reduces snagging, dragging and tripping hazards

Y-Lanyards for 100% tie-off while climbing or transversing



Your choice of hooks:

- 5/8 in. (16 mm) Double Lock Hook
- 2 1/4 in. (57 mm) Form Hook
- 2 1/2 in. (64 mm) Ladder Hook
- Shown with Shock Pack

FALL PROTECTION

MATERIAL HOISTING

WIND ACCESS

SERVICE EXPERTISE

FORMS, APPLICATIONS & DOCUMENTS

APPENDIX

OVERVIEW

HARNESSES

CONNECTING DEVICES

ANCHORAGE CONNECTORS

VERTICAL LIFELINES

TEMPORARY HORIZONTAL LIFELINE SYSTEMS

SPIDERRAIL™

NETTING

ROOF SAFETY

WELDING PRODUCTS





Rescue Ring

primary safety line.





Built into all 6 ft (1.8 m) lanyards for safe worker retrieval

Rescuer connects the rescue safety line to the rescue ring and releases the connector to the rope grab on the

100% tie off is achieved during rescue.

Ladder Hook

Double Lock Snap Hook

Form Hook

Shock-Absorbing Lanyards (Options and Part Numbers)

Match your desired hook with your desired lanyard to find the part number.

	3 ft (0.9 m) Web	6 ft (1.8 m) Web	6 ft (1.8 m) Y-Web	6 ft (1.8 m) Internal Web	6 ft (1.8 m) Internal Y-Web
Double Lock Hook	707784-1	707794-1	707791-1	707789-1	707790-1
Form Hook	707784-2	707794-2	707791-2	707789-2	707790-2
Ladder Hook	707784-3	707794-3	707791-3	707789-3	707790-3